


14. Java Object Orientation

Classes, Inheritance, Encapsulation

Object Orientation: Different Aspects




427

428

Already discussed: Objects


Focus on *Object* of a data type that contain

- Data (Fields) and
- Code (Methods)



429

Already discussed: *Composition* of Objects




430

Inheritance

Data types are part of a type hierarchy

Subtypes inherit data and code from their *supertypes*.



431

Inheritance \neq Composition

Composition: An object contains fields that refer to objects of a different type

Inheritance: An object of some type contains additional fields and methods that are inherited from a supertype

432

Correct Use for Inheritance

Important question to identify whether DataType1 should inherit from DataType2:

Is DataType1 a DataType2?

Example

- *Is* a "Student" a "Person" ✓
- *Is* an "Apple" a "Fruit" ✓

433

Correct Use for Composition

Important question to identify whether DataType1 should contain DataType2 as composition:

Has DataType1 a DataType2?

Example

- *Has* a "Student" an "Address" ✓
- *Has* an "Apple" a "Color" ✓

434


Inheritance: extends Keyword

```
class Measurement {
    LocalDateTime datetime;
    Koordinate position;

    boolean alarm() {...}
}

class Temperature extends Measurement {
    double temperature;
}

class Wind extends Measurement {
    double speed;
    double direction;
}
```




435

Data Encapsulation (Repetition)

Control, what data and what code can be *accessed* from where.

Access modifiers:

- **private**: Visible only from code within the same class
- **protected**: Visible from code in the same class or a subclass
- **public**: Visible from everywhere



436


Example for protected Visibility

```
class Measurement {
    private LocalDateTime datetime;
    protected Koordinate position;

    public boolean alarm() {...}
}

class Temperature extends Measurement {
    private double temperature;
}

class Wind extends Measurement {
    private double speed;
    private double direction;
}
```



437

Abstract Classes

```
class Measurement {
    ...
    // returns 'true' if measurement is alarming, 'false' otherwise
    public boolean alarm() {...}
}
```

- Class Measurement provides a method alarm()
- The method should return **true** *iff* the measurement is *alarming* ...
- ... *but the implementation of the method depends on the implementation of the different subtypes ... ?!*

438

Abstract Classes

It doesn't make sense to create objects of type `Measurement`, it should be *abstract*.

Abstract Classes: Keyword `abstract`

```
abstract class Measurement {
    ...
    // returns 'true' if measurement is alarming, 'false' otherwise
    abstract boolean alarm();
}

class Temperature extends Measurement {
    double temperature;

    // Implement the abstract method from the supertype
    boolean alarm(){
        return temperature > 35;
    }
}
```

439

440

Abstract Classes: Keyword `abstract`

```
abstract class Measurement {
    ...
    // returns 'true' if measurement is alarming, 'false' otherwise
    abstract boolean alarm();
}

class Wind extends Measurement {
    double speed;

    // Implement the abstract method from the supertype
    boolean alarm(){
        return speed > 80;
    }
}
```

441

Abstract Classes: Properties

- If at least one method is `abstract`, that is, not implemented, the whole class has to be declared `abstract`.
- Abstract classes *can't* be instantiated (`new ...`)
- Abstract classes contain data and code that is inherited by all subtypes. The differences are abstracted.

442

Abstract Classes: Usage

```
Temperature t = new Temperature(40);  
boolean b = t.alarm();
```

⇒ In his example, the variable `b` is set to `true`.

What if we call `alarm()` *from a method defined in class Measurement?*

443

Abstract Classes: Dynamic Method Binding

```
abstract class Measurement {  
    abstract boolean alarm();  
  
    String alarmOutput(){  
        if (this.alarm()){  
            Out.println("Alarm!");  
        } else {  
            Out.println("Nominal");  
        }  
    }  
}
```

444

Abstract Classes: Dynamic Method Binding

```
Temperature t = new Temperature(40);  
t.alarmOutput();
```

⇒ Output: "Alarm!"

- The object `t` of type `Temperature` inherited the method `alarmOutput`.
- In this object, the implementation from method `alarm()` in Class `Temperature` is bound to the abstract method `alarm()`.
- Thus, `alarmOutput()` will call the implementation from `Temperature`.

445