Referenzen

```
#include <iostream>

void banner_line (unsigned int& n)
{
  while (n > 0) {
    std::cout << "*";
    --n;
  }
  std::cout << "\n";
}


int main ()
{
  for (unsigned int n=1; n<5; ++n)
    banner_line (n);

  return 0;
}
```

Was gibt `main` aus?

1. ```
   *
   **
   ***
   ****
   ```
2. ```
   *
   *
   *
   *
   ```
3. ```
   *
   *
   *
   ```
   ... (terminiert nicht)
4. kann gar nicht kompiliert werden
   ```

Referenzen

```
#include <iostream>

void banner_line (unsigned int& n)
{
  while (n > 0) {
    std::cout << "*";
    --n;
  }
  std::cout << "\n";
}


int main ()
{
  for (unsigned int n=1; n<5; ++n)// n == 1
    banner_line (n);// setzt n auf 0

  return 0;
}
```

Was gibt `main` aus?

1.
```
*
**
***
****
```
2.
```
*
*
*
*
```
3.
```
*
*
*
```
... (terminiert nicht)
4. kann gar nicht kompiliert werden

Referenzen

```
#include <iostream>

void banner_line (unsigned int& n)
{
  while (n > 0) {
    std::cout << "*";
    --n;
  }
  std::cout << "\n";
}


int main ()
{
  for (unsigned int n=1; n<5; ++n)// n == 1
    banner_line (n);// setzt n auf 0

  return 0;
}
```

Was gibt `main` aus?

1.
```
*
**
***
****
```
2.
```
*
*
*
*
```
3.
```
*
*
*
```
... (terminiert nicht)

4. kann gar nicht kompiliert werden